



Badger Meter

Data Industrial® 340 BN/MB Btu Energy Transmitter

OVERVIEW

The Data Industrial 340 BN/MB Btu Energy Transmitter from Badger Meter is an economical, compact device for sub-metering applications utilizing the BACnet™ or Modbus® communications protocol.

The 340 BN/MB Btu Energy Transmitter calculates thermal energy using the signal from a flow sensor installed in a hydronic heating or chilled water system, and the signals from two 10 kΩ temperature thermistors, 100 Ω RTDs or 1000 Ω RTDs installed in the system's inlet and outlet points. The flow input may be provided by any Data Industrial sensor and many other pulse or sine wave signal flow sensors.

The on-board microcontroller and circuitry make precise measurements and produce accurate, drift-free outputs. The 340 BN/MB Btu Energy Transmitter is programmed using Badger Meter Windows® based software. Calibration information for the flow sensor type and pipe size may be preselected or entered by the user in the field. While the unit is connected to a PC or laptop computer, real-time flow rate, flow total, temperatures, energy rate and energy total are available.


EXAMPLE:	340 BN/MB	-	xx
SERIES			
Btu Energy Transmitter w/output	340 BN/MB		
OPTIONS			
Transmitter Only			00
With Metal Enclosure			02
With Plastic Enclosure			03
With DIN Rail Mounting Clips			04

340 BN/MB Ordering Matrix

The 340 BN/MB Btu Energy Transmitter features three indicator LEDs to verify the sensor input signal, network link and pulse output.

The 340 BN/MB Btu Energy Transmitter communicates via RS485.


The compact cast body measures 3.65 x 2.95 inches (93 x 75 mm) and can be easily mounted on panels, DIN rails or enclosures.




SPECIFICATIONS

Power
Power supply:
<ul style="list-style-type: none"> 12-24V AC rms 12-24V DC
Current draw: 115 mA at 12V DC
Flow Sensor Input
Pulse type sensors:
Signal amplitude: 2.5V DC threshold
Signal limits: Vin < 35V (DC or AC peak)
Frequency range: 0 to 10 kHz
Pull-up: 15V DC @ 2k Ω Source Impedance
Sine wave sensors:
Signal amplitude: 30 mV p-p threshold
Signal limits: Vin < 35V (DC or AC peak)
Frequency: 0 to 10 kHz
Power out terminal:
15V DC \pm 1V DC @ 500 Ω Source Impedance
Temperature Sensor (2 of same type required) Input
<ul style="list-style-type: none"> 10k Ω thermistor, 2 wire, type II, 10k Ω @ 25°C 100 Ω platinum RTD, DIN calibration curve, conforms to IEC-751 Standard 1000 Ω platinum RTD, DIN calibration curve, conforms to IEC-751 Standard
Calibration range of measurement: 0 to 150°C
Communication Port
<ul style="list-style-type: none"> RS-485 with termination, pull up and pull down jumpers
Pulse Output
<ul style="list-style-type: none"> Isolated solid state switch in any standard or custom total units Adjustable 50 ms to 1.0 second pulse output width in 50 ms increments Maximum sinking current: 100 mA @ 36V DC
Operating Temperature
<ul style="list-style-type: none"> 0°C to +70°C +32°F to +158°F
Storage Temperature
<ul style="list-style-type: none"> -40°C to +85°C -40°F to +185°F
Weight
<ul style="list-style-type: none"> 4.8 oz. with connector headers installed

Sensor Calibration
Badger Meter: Use K and offset values provided in sensor manual
Other Sensors: Check with respected manufacturer of flow sensor and with factory
Units of Measure
Flow Measurement:
Rate: gpm, gph, l/sec, l/min, l/hr, ft3/sec, ft3/min, ft3/hr, m3/sec, m3/min, m3/hr
Total: Gallons, Gallons X 100, Gallons X 1000, Liters, Cubic Feet, Cubic Meters
Energy Measurement
Rate: kBtu/min, kBtu/hr, kW, MW, hp, tons
Total: Btu, kBtu, MBtu, kWh, MWh, kJ, MJ
Temperature Measurement
<ul style="list-style-type: none"> Fahrenheit, Centigrade
Programming
<ul style="list-style-type: none"> Requires PC or laptop running Windows 2000, XP, Vista or Windows 7 Data Industrial 340BN/MB Programming Kit containing software and Data Industrial Series A-301 programming cable is required for programming and setup



Plastic Enclosure Dimensions



Metal Enclosure Dimensions



Please see our website at www.badgermeter.com for specific contacts.

Data Industrial is a registered trademark of Badger Meter, Inc.

Other trademarks appearing in this document are the property of their respective entities.

Copyright 2011, Badger Meter, Inc. All rights reserved.

Due to continuous research, product improvements and enhancements, Badger Meter reserves the right to change product or system specifications without notice, except to the extent an outstanding contractual obligation exists.

Badger Meter | P.O. Box 245036, Milwaukee, Wisconsin 53224-9536

800-876-3837 | infocentral@badgermeter.com | www.badgermeter.com